

conflicting signs must be covered or removed, so it is important to identify any possible issues before implementation.

- Sign messages must not be permitted to be formed with tape, for example, Lane Status signs and mocking speed numerals in tape.
- Sign support structures must not be left in place without signs attached.

For merge tapers where the posted permanent speed limit of the road is 80 km/h or greater, the sign spacing between the lane status sign and the start of the merge taper may be increased to a distance of two sign spacings.

For merge tapers at any speed limit, where more than one lane is being closed, the sign spacing between the lane status sign and the start of the initial merge taper may be increased to a distance of two sign spacings.

A distance plate (TC2287) may be added to the lane status multi message sign to indicate the distance from the lane status sign to the start of the merge taper.

If sign duplication is not possible and the designer has chosen to repeat signs on the one side of the road, repeated signs are located a minimum of one sign spacing from the original sign.

If there are spacing requirements between the original sign being repeated and another sign, device, or hazard beyond the sign (in the direction of travel), then this spacing requirement will now apply to the repeated sign. Any spacing requirements between the original sign being repeated and another sign, device, or hazard prior to the sign (in the direction of travel), will remain as a requirement to the original sign being repeated.

See Figure 2.5.3(b) for an example showing signs for one direction of travel only on a two-way road. This figure does not include all traffic control devices required and is not to be used as a TGS diagram.