

2.5.7 Traffic lanes

Difference

Replace Table 2.4 with the following:

Table 2.4 – Desirable number of lanes for each direction

Mid-block (one direction) (vph)	Within 200 m of controlled intersection (one direction) (vph) [^]	Desirable number of open lanes for direction considered
≤ 1000	≤ 500*	1
1001–2000	501–1000	2
2001–3000	1001–1500	3
3001–4000	1501–2000	4

* Right turns out of the single lane may need to be prohibited, depending on the proportion of heavy vehicles and the volume of opposing traffic.

[^] This is a controlled intersection where traffic in the directions being considered is controlled (by traffic signals, roundabout, GIVE WAY or STOP signs).

NOTE: Volumes shown in the Table may need to be reduced by the amount shown if the following apply:

- Pavement surface is rough or unsealed – reduce traffic volume by 30%.
- Horizontal geometry through the restriction is reduced to a speed value of less than 40 km/h – reduce volume by 50%.
- Volume of heavy vehicles exceeds 10 % and downward, level or easy upgrade – reduce traffic volume by 20%.
- Volume of heavy vehicles exceeds 10 % and sustained upgrades > 5% – reduce traffic volume by 40%.

2.5.8 Lane widths

Difference

Replace the entire Section 2.5.8 with the following:

Lanes carrying traffic around, through or past a roadworks site must be as per Table 2.5. Lane widths should consider accommodating the swept path of large vehicles expected to negotiate the roadworks site.