

- c) if adjusting timings is not successful in managing queue lengths, implement a pre-designed contingency plan to cater for the longer queue lengths being experienced – this will need to be completed by the traffic management implementer while traffic controllers continue to control traffic, and
 - d) if a pre-designed contingency plan is not provided, seek urgent advice from the traffic management designer for the works.
8. Where the speed limit on approach to the traffic control station is greater than 60km/h, a 60 km/h speed zone must be commenced at least one sign spacing (Table 2.2) in advance of the primary PREPARE TO STOP sign. This does not apply to situations where the traffic control station is located down a side road and the speed of traffic on approach to the traffic control station and the end of the traffic queue is less than 60 km/h through other controls (such as the traffic needing to turn onto the side road at a lower speed). Speed signs may be required on the side road if the speed of traffic on the side road may exceed 60km/h prior to the traffic control station or the end of the traffic queue. See Section 4.8.1 for more information on speed limits for traffic control stations on a through road near a side road.
- Duplicate the speed limit signs on both sides of the road and install repeater speed limit signs as required in Section 5.5.1.
9. Where intersections are located within the advance warning area (between the traffic control station and the ROADWORK AHEAD or VMS sign), see Section 4.8.1 for the signing requirements for traffic on or entering from side roads.
10. Provide additional devices and methods for avoiding end-of-queue collisions as required in Section 4.8.3.
11. For shuttle flow operations, the traffic control taper must start a minimum of 6 m from the traffic control station.

As per AGTTM Part 7 Section 2.6.3, when used in a multi-message situation, the PREPARE TO STOP panel must be placed closest to the travel way and that the 600 x 600 version of this sign is used as illustrated in Figure 4.8(b), excluding where the use of the 1200 x 300 version is specifically permitted by QGTTM.

Figure 4.8(b) – Multi message sign assembly examples (sign located on left side of the road)

