

4.8.1 Intersections within the advance warning area

New

Where intersections exist within the advance warning area (between the traffic control station and the ROADWORK AHEAD or VMS sign), the following warning sign arrangements must apply.

Where the intersection is located between:

- i. the primary PREPARE TO STOP sign and the ROADWORK AHEAD sign or VMS, an additional ROADWORK AHEAD sign or VMS must be located on the side road and should be a minimum distance of a single sign spacing from the intersection (see Figure 4.8.1(a))
- ii. the predicted end-of-queue location and the primary PREPARE TO STOP sign, either:
 - a) an additional primary PREPARE TO STOP sign must be located on the side road and should be a minimum of a single sign spacing from the intersection and a ROADWORK AHEAD sign, or VMS must be positioned in advance of this sign and should be located a minimum of a single sign spacing further down the side road (see Figure 4.8.1(b)), or
 - b) an additional PREPARE TO STOP sign must be provided as a repeater on the through road and should be located a minimum of 15 m along the through road after turning from the side road, travelling towards the traffic control station, and a ROADWORK AHEAD sign or VMS must be located down the side road and should be a minimum of a single sign spacing from the intersection (similar to Figure 4.8.1(c), but with the end of queue located after turning from the side road towards the traffic control station).
- iii. the traffic control station and the predicted end-of-queue location, either:
 - a) an additional primary PREPARE TO STOP sign must be located on the side road and should be a minimum of a single sign spacing from the intersection, and a ROADWORK AHEAD sign or VMS must be positioned in advance of this additional PREPARE TO STOP sign and should be located a minimum of a single sign spacing further down the side road (similar to Figure 4.8.1(b), but with the queue extending past the side road) or