

- Where environmental or geometric issues exist that limit visibility or impact normal stopping distances such as poor weather conditions (for example rain or fog), poor road conditions, a downhill approach, vertical curves, night works (driver fatigue or visibility) or a slippery road surface are present.
- Where significant volumes of heavy vehicles are present or expected.

4.8.4 Queued traffic ahead multi-message sign

New

The Queued traffic ahead multi-message sign assembly (see Figure 4.8(a)) may be used at other locations (in addition to on approach to traffic control stations) where the temporary warning of traffic congestion is desirable.

4.9 Termination Area

Addition

Additional guidance is provided in Section 5.12.

4.10 Vulnerable Road Users

4.10.1 Pedestrians

Difference

Replace the two dot points:

- Desirably, if footpaths or pedestrian crossings have been partially closed or temporarily relocated, a temporary footpath should be provided with minimum width of 1.8 m to allow for all pedestrians including those with mobility aids or on the same scale and to the same width as any facilities for pedestrian that existed prior to the works. This width should also be applied to any temporary ramps (e.g. kerb ramps). If these widths are not practicable, alternative routes must be provided with a firm smooth surface and no trip hazards in the following order of preference:
 - 1 on the side of a road reserve away from traffic
 - 2 between the work area and road but not in a traffic lane
 - 3 onto the road either in a lane used for parking or a delineated and protected section of an existing traffic lane