

For additional guidance on road safety barriers in Queensland, see the [Road Planning and Design Manual Edition 2: Volume 3, Supplement to Austroads Guide to Road Design Part 6: Roadside Design, Safety and Barriers](#), with Section 6.8 of this document detailing the requirements for temporary road safety barriers.

Only road safety barriers included on the current list of products in the Transport and Main Roads [Accepted Road Safety Barrier Systems and Devices document](#) must be used at roadwork sites in Queensland.

The Austroads Safety Hardware Training and Accreditation Scheme (ASHTAS) will, over time, offer courses for Safety Barrier Operative (Entry Level), Installers (Permanent and Temporary Safety Barriers), Designers (Permanent and Temporary Safety Barriers), and more. See QGTTM Part 8 Section 5.5.12 for more details.

For more ASHTAS details see the departmental web page [Austroads Safety Hardware Training and Accreditation Scheme \(ASHTAS\)](#).

5.3.2 Containment fence

Difference

Replace:

Note that metal star pickets should not be used in situations where they are directly exposed to traffic or any environment where they may be hit by a vehicle.

with:

The use of star pickets must be in accordance with Section 6.12.

5.3.3 Visibility screens

Addition

For additional guidance on anti-gawking screens, see the *Guideline – Traffic Management at Works on Roads*.

5.4 Delineate the route

Difference

Replace:

If narrower edge clearance is required, obtain approval from the relevant road infrastructure manager.