

If it is not practicable or possible to terminate the temporary speed limit beyond the temporary speed zone by the above methods, the END Speed Limit sign (R4-12) may be used. An example of this is where the default speed limit (typically on rural roads), road surface, alignment or other conditions will not allow the road user to travel safely at that speed. It is a legal requirement that a speed zone is terminated by:

- another regulatory speed control sign or END Speed Limit sign
- other means of traffic regulation imposed by the State.

Operational

The following apply when installing speed signs:

- Any permanent speed signs that contradict the temporary speed limit in the required zone must be covered or removed.
- Any advisory speed signs higher than the temporary speed limit in the required zone must be covered.
- Speed Restriction signs where required to be duplicated in the 'Designing the speed limit' section should be placed on both sides of the roadway where practicable to ensure road users have clear visibility of speed limit signs.
- Temporary speed limit signs should be used together with other appropriate devices already required by other site conditions. For example, display temporary speed limit signs used for.
- worksite protection and safety in conjunction with the Workers (symbolic) sign.
- All speed limits related to road worker safety must be removed or covered when road workers, traffic controllers or plant are not on site.
- Speed limits when road workers, traffic controllers and plant are not on site should be determined with consideration of the safe passage of road users. If no hazard to road users exists, the speed limit should be returned to the permanently posted speed limit.
- Any gantries within the worksite with Variable Speed Limit or Lane Control signs must be programmed to display the temporary speed limit or turned off. Check the TMP for guidance on other large permanent signs and variable speed limit signs.
- A record of dates and times temporary speed limits are in operation must be kept, including any changes made, the name of personnel installing, changing or removing signs (see Section 2.5.3).
- Workplace safety must be considered during set-up and dismantling of signs.