

with:

- Merge tapers must not start or end:
 - within 50 m of an intersection (both approach and departure sides) on a controlled leg of an intersection on a Category 2 road
 - within 100 m of an intersection (both approach and departure side) located on a ramp from / to a Category 3 road, or
 - within 100 m of a ramp (on or off) on a Category 3 road.
- Merge tapers located on an uncontrolled leg of an intersection on a Category 2 road should not start or end within 50 m of the intersection (both approach and departure sides).
- Merge tapers must not be implemented through / across an intersection or ramp.
- Lateral shift tapers (excluding at contraflow transition points) must not be implemented through / across an intersection or ramp. Where provided at contraflow transition points, the management of the other approaches to the intersection will be critical.

Addition

In subsection '**Designing a taper**', add the following:

When considering the space requirements for a merge taper, the terminology referring to a controlled leg or uncontrolled leg of an intersection on a Category 2 road is different to a controlled intersection. Controlled legs are those approaches to an intersection controlled by traffic signals, roundabout give way signs, give way signs, or stop signs. In some cases, a controlled intersection may have uncontrolled legs, which are not subject to any formal control method.

Figure 5.9.1(c) shows an example of a merge taper on a Category 2 road with a 60 km/h speed limit that includes intersections with minor side streets (GIVE WAY or STOP signs on the side streets only). The side street legs are controlled while the multilane road has uncontrolled legs through these controlled intersections.