

Section 4.8 for advance sign options). For PTCD, the Traffic Controller (symbolic) sign must be replaced with the relevant PTCD (symbolic) sign.

16. Apply a temporary speed limit of 60 km/h or less if speed is above 60 km/h (see Section 5.5.1) on approach to the PTCD.
17. PTCDs must be regularly monitored to ensure they are operating effectively and safely by checking that:
 - a) the time settings are appropriate
 - b) the alignment of the signal displays is appropriate for the speed zone
 - c) the associated signs are intact and properly displayed
 - d) detectors are functioning correctly
 - e) there are no burnt out lanterns, and
 - f) batteries are charged.

Figure 5.23 illustrates an example of PTCD and sign placement. This diagram does not include all traffic control devices required and is not to be used as a TGS diagram (see Section 4.8 for avoiding end-of-queue collision options and placement of signs). The speed of traffic must be reduced to a maximum of 60 km/h on the approach to a PTCD and an advance warning sign (ROADWORK AHEAD) is to be located in accordance with Section 4.8.

PTCDs may be used on any road environment; however, PTCDs should be used in lieu of traffic controllers using a STOP / SLOW bat on all roads with an annual average daily traffic (total vehicle count in both directions of travel per day) of over 500 vehicles per day and a permanent posted speed limit of 70 km/h or greater.

Where a PTCD is not used as recommended here, a risk assessment in accordance with the requirements of Clause 1.9 of the Queensland MUTCD Part 3 must be undertaken. See also the risk assessments requirements for using TC's in place of PTCDs, in the *Guideline – Traffic Management at Works on Roads* Chapter 5 Section 2.2.

Only PTCDs included on the current list of approved products in the Transport and Main Roads [ITS Approved Products document](#) must be used at roadworks sites in Queensland.

Additional guidance on the use, installation and operation of PTCDs, including Type 1 and 2 PTSS and boom barriers, is available in the *Guideline – Traffic Management at Works on Roads*.