

- The traffic control station and the area where traffic controllers are operating PTCDs from must be well illuminated at night. Where required, provide additional lighting. See Section 6.7 Night works for greater detail about working at night.
- Relieve traffic controllers from traffic controller duties at least every 2 hours for at least 15 minutes.
- If cone tapers are used, position the traffic controller 6 m in front of the taper on the left-hand shoulder or edge of the road and facing approaching traffic.
- Place four traffic cones spaced 4 m apart, on the centre-line 6 m in front of the traffic controller position.
- If there is a queue, traffic controllers can move to the driver's side when safe to do so to remain visible to all road users.
- Under no circumstances are traffic controllers to stand or operate unprotected in a lane carrying traffic.
- Traffic controllers are to only communicate with a road user once the vehicle has stopped and is safe to do so.
- A single traffic controller must never control more than one lane of traffic or more than one approach when using a STOP/SLOW bat or a PTCD. This may only be varied where a traffic controller is using a PTCD which is capable of alternative arrangements and both the device and manner of operation is approved by the department. See Section 2.6.2 of AGTTM Part 7 for additional requirements and considerations when designing and using PTCDs for traffic control.
- Provide a traffic controller at intersections to guide road users entering from a side road.
- Some intersections require three or more traffic controllers. Where multiple traffic controllers are used they are required to:
 - 1 ensure that road users are not seeing conflicting message from other traffic controllers at different locations of the worksite
 - 2 be in continuous radio contact with each other when they are not visible to each other.

For detailed guidance on traffic controllers see AGTTM Part 7.