

6 Design for additional issues

6.5 *Shoulder as a Temporary Lane*

Difference

Replace:

- moving road users to the shoulder may bring roadside hazards within the clear zone.

with:

- moving road users to the shoulder may bring roadside hazards within the clear zone. See Section 6.11 for details on the clear zone.

6.6 *Pavement markings*

Addition

The methods specified in [Transport and Main Roads Technical Specification](#) MRTS45 *Road Surface Delineation* must be used to cover or remove line marking / pavement marking. In addition to the methods in MRTS45, the use of proprietary line marking tape may be used to either temporarily cover or install temporary line marking / pavement marking.

6.7 *Night works*

Difference

Replace the entire Section 6.7 with the following:

Undertaking work at night is effective in reducing delays to traffic because traffic volumes are normally lower than during most daylight hours; however, work at night requires careful additional planning and inspection.

The following are in addition to the requirements in AS 1742.3 Clause 4.2.4 *Night conditions*.

When planning night-time traffic management measures, the following considerations apply:

1. many visual cues available during the day are not available to drivers at night
2. TMA(s) may be used to increase visibility and provide forward warning to motorists as well as protecting workers
3. noise limitations
4. traffic demand will be lower, so traffic speed may increase
5. road user and road worker visibility are reduced