

6.10 Placement and operation of Portable Variable Message Sign (VMS)

Addition

Insert lead in sentence to this Section:

Please note Portable Variable Message Signs (VMS) referred to in this section, are referred to as Temporary Variable Message Signs (TVMS) in Queensland.

6.10.1 Principles and guidance

Addition

The requirements for TVMSs apply to both trailer-mounted VMS and vehicle-mounted VMS.

The need for a TVMS will be determined by either technical documents (including the *Queensland Manual of Uniform Traffic Control Devices* (Queensland MUTCD), or *Queensland Guide to Temporary Traffic Management* (QGTMM) or contract documents such as Technical Specification MRTS02 *Provision for traffic*) or by a risk assessment.

The longitudinal and lateral placement requirements for a TVMS are subject to the requirements of Sections 6.10.3 and 6.10.4 and a risk assessment.

6.10.2 Aiming distance

Difference

Replace:

Wherever practicable, a VMS should be aimed to the centre of the nearest lane for approaching traffic, using the desirable aiming distance specified in Table 6.1 below, and as shown in Figure 6.2. If the VMS displays two screens, more distance is required for motorists to read and comprehend the sign.

with:

Wherever practicable, a VMS should be aimed to the centre of the nearest lane for approaching traffic, using the desirable aiming distance specified in Table 6.2 below, and as shown in Figure 6.1. If the VMS displays two screens, more distance is required for motorists to read and comprehend the sign.

Addition

The TVMS aiming distances (Table 6.2) and angle to approaching vehicles (Figure 6.1) are recommendations which may need to be modified based on the design and visibility characteristics of the message on the TVMS, and the road geometry. See Section 6.10.7 for the drive through requirements.