

6.10.7 Drive through requirements

New

Legibility and readability of the TVMS must be confirmed using a 'drive through' of the site. If there are two alternating screens on the TVMS, ensure both screens can be easily read while travelling at the speed limit on approach. It may be necessary to adjust the aiming distance, angle of the TVMS to traffic and screen timing to ensure the message(s) on the TVMS are both legible and readable.

6.10.8 TVMS specification

New

TVMSs must be manufactured in accordance with the Transport and Main Roads Technical Specification MRTS262 *Temporary Variable Message Signs*.

6.10.9 Display of messages on TVMSs

New

The use of the TVMS to display roadside signs or text messages must be in accordance with the Queensland MUTCD Clauses 4.22 *Variable message signs used at roadworks* and 4.24 *Display of electronic signs*.

6.11 Clear Zone

New

This section on clear zones will apply when clear zones are identified as being required elsewhere in the TTM technical documents. Typically, clear zones will apply to stored plant or materials (see Section 7.4.1), and when traffic is laterally shifted onto a different alignment (see Section 6.5).

The identification of hazards is generally based on the use of the clear zone concept to define the area beside the road that is of most interest in terms of roadside safety.

A clear zone is the area adjacent to the traffic lane that should be kept free from features that would be potentially hazardous to errant vehicles. The clear zone is a compromise between the recovery area for every errant vehicle (allowing a driver to stop safely or safely regain control of a vehicle that has left the road), the cost of providing that area and the probability of an errant vehicle encountering a hazard. The clear zone should be kept free of non-frangible hazards where economically and environmentally possible.

Alternatively, hazards within the clear zone should be treated to make them safe or be shielded by a safety barrier.