

It is important that careful consideration is given to how star pickets are used because if used incorrectly they may present a safety hazard.

The use of star pickets must be supported by a risk assessment.

In addition, the use of star pickets is subject to the following:

- Star pickets must not be used within 1 m of the edge of the traffic lane on roads with speed limits of 80 km/h or more.
- Star pickets should not be used within 1 m of the edge of the traffic lane on roads with speed limits of less than 80 km/h.
- Star pickets must be fitted with end caps to reduce the potential of piercing injuries.
- Star pickets must be inspected regularly as per the inspection requirements for temporary traffic management devices, and if they are bent or damaged, they must be replaced or repaired immediately.
- Star pickets must be installed vertically, as installing them at an angle may result in a spearing hazard.
- Star pickets are generally black but may be any colour.
- The presence of underground services must be checked before installing star pickets.
- Star pickets must not be used to support standard signposts by placing a post over the top of an installed star picket.
- Star pickets should be delineated when they are installed within 3 m of traffic, pedestrian or cyclist paths.

7 How to apply the Traffic Guidance Scheme

7.3 Installation

Difference

Replace:

When designing a TGS, the designer must consider and document the process for installing traffic control devices.

with:

When designing a TGS, the designer must consider and document the process and order for installing traffic control devices.