

4 Works on road – within traffic lane

4.1 Work protected by specialist vehicles

4.1.2 Truck-mounted attenuators

Addition

Add after the 4th paragraph:

The TMA clear distance must not be reduced to a value below 40 m.

Addition

Only TMAs included on the current list of accepted products in the Transport and Main Roads [Accepted Road Safety Barrier Systems and Devices](#) document must be used at roadwork sites in Queensland.

4.2 Works between gaps in traffic

4.2.2 Criteria

Addition

Add the following to the Notes for Table 4.1:

If the work vehicle and equipment in criteria 7 are parked where parking would be legal and the safety of other road users is not compromised, answer 'yes' to this criterion.

Addition

If a lookout person is in use, and a vehicle-mounted warning device is applicable (see Section 4.2.5 for examples where the vehicle-mounted device is not required), the minimum sight distance from approaching road users to the vehicle-mounted warning device must be as per the sight distance requirements for lookouts in Table 4.3.

4.2.3 Traffic control devices

Difference

Replace entire Section 4.2.3 with the following:

Refer to Section 3.4 for vehicle mounted warning device requirements.

4.2.4 Pre-installation processes

Addition

If a TGS is provided, confirm the TGS has been signed off by relevant personnel, with a copy of the TGS onsite at all times during the works.