

4.2.5 Installation (TGS instruction)

Addition

A TGS may be developed and included in a generic TGS selection system for works between gaps in traffic activities.

Addition

In the subsection '**Operation**', add the following:

The work vehicle is parked clear of moving traffic lanes or parked where parking would be legal, and the safety of other road users is not compromised.

When using lookouts in Queensland, additional guidance and requirements for the Lookout Protection Method, in the [Guideline – Traffic Management at Works on Roads](#) must be applied.

Difference

In the subsection '**Operation**', replace the note under Table 4.3:

Note: *These distances are based on a maximum distance of 3.5 m between road workers' location and their escape to a shoulder or median. For longer escape routes seek specialist design guidance as additional sight distance will be required.

with

Note: *These distances are based on a maximum distance of 3.5 m between road workers' location and their escape to a shoulder or median. For longer escape routes additional sight distance will be required and the sight distance provisions for the Lookout Protection Method, in the [Guideline – Traffic Management at Works on Roads](#) must be applied.

4.3 Short term works in traffic

4.3.3 Traffic control devices

Difference

Replace entire Section 4.3.3 with the following:

Refer to Section 3.4 for vehicle mounted warning device requirements.

4.3.4 Pre-installation processes

Addition

If a TGS is provided, confirm the TGS has been signed off by relevant personnel, with a copy of the TGS onsite at all times during the works.