

4.3.5 Installation (TGS instruction)

Addition

A TGS may be developed and included in a generic TGS selection system for short term works in traffic activities.

Difference

In the subsection '**Operation**', replace:

At all times when conducting these activities, the lookout person and worker must be within a reasonable proximity (no more than 40 m) of the vehicle with a vehicle mounted warning device, which is parked clear of traffic lanes.

with:

At all times when conducting these activities, the lookout person and worker must be within a reasonable proximity (no more than 40 m) of the vehicle with a vehicle mounted warning device, which is parked clear of traffic lanes or parked where parking would be legal, and the safety of other road users is not compromised.

Addition

In the subsection '**Operation**', add the following:

When using lookouts in Queensland, additional guidance and requirements for the Lookout Protection Method, in the [Guideline – Traffic Management at Works on Roads](#) must be applied.

Difference

In the subsection '**Operation**', replace the note under Table 4.6:

Note: *These distances are based on a maximum distance of 3.5 m between road workers' location and their escape to a shoulder or median. For longer escape routes seek specialist design guidance as additional sight distance will be required.

with:

Note: *These distances are based on a maximum distance of 3.5 m between road workers' location and their escape to a shoulder or median. For longer escape routes additional sight distance will be required and the sight distance provisions for the Lookout Protection Method, in the [Guideline – Traffic Management at Works on Roads](#) must be applied.