

Addition

In the subsection '**Operation**', add the following:

When using lookouts in Queensland, additional guidance and requirements for the Lookout Protection Method, in the [Guideline – Traffic Management at Works on Roads](#) must be applied.

Difference

In the subsection '**Operation**', replace the note under Table 4.8:

Note: *These distances are based on a maximum distance of 3.5 m between road workers' location and their escape to a shoulder or median. For longer escape routes seek specialist design guidance as additional sight distance will be required.

with

Note: *These distances are based on a maximum distance of 3.5 m between road workers' location and their escape to a shoulder or median. For longer escape routes additional sight distance will be required and the sight distance provisions for the Lookout Protection Method, in the [Guideline – Traffic Management at Works on Roads](#) must be applied.

4.5 Constantly moving work area – in lane

4.5.1 Description

Addition

Add the following note to Figure 4.5:

Advance warning signs are required in both directions for two-lane, two-way roads and undivided multilane roads.

4.5.2 Criteria

Addition

The minimum sight distance from approaching road users to the vehicle-mounted warning device must be as per the sight distance requirements for lookouts in Table 4.11.

4.5.3 Traffic control devices

Difference

In the subsection '**Vehicle mounted warning device**', replace entire subsection with the following:

Refer to Section 3.4 for vehicle mounted warning device requirements.