

5.4.6 Close out process

New

Daily records

Daily records of the site layout including devices, risk assessments, sight distances, signs or TGS (if required), must be kept in a diary or in work sheets, which must be retrievable upon request.

Reference to the diagram number which generally applies to the layout used or to a documented procedure is usually sufficient. Any significant departures from, or additions to, the signs and devices included in the relevant diagram(s) should be noted and approved.

Incidents

In the case of incidents (for example, crashes, collisions), either witnessed or reported, involving the public or from which legal proceedings might arise, the actual type, size and location of signs and devices in use at the time of the accident must be recorded with the site layout and sign arrangement photographed for subsequent reporting. Details of the actual width and condition of the travelled path and weather conditions should also be recorded.

6 Investigations, inspections, road lighting or signal works

6.1 Investigations and inspections

6.1.1 Description and criteria

New

Prior to undertaking these work activities, a risk assessment must be undertaken to ensure the works can be safely completed. Risk considerations are outlined in Section 2.2.1.

For activities associated with investigations or inspections, including the viewing or measuring a section of roadway or road feature (for example, for maintenance or planning purposes), or a similar activity where road works are not being undertaken, no specific TTM controls are required where:

- a) the activity is clear of the roadway: the exception to this would be where the activity is carried out while crossing the road, for example, measuring the lane width – if the activity cannot be carried out while crossing the road and may take longer to complete, the works may be undertaken in accordance with Section 4.2 (work between gaps in traffic)