

Visibility

Visibility of the PTCD is a key consideration when designing traffic guidance schemes. The Traffic Management Designer should consider the following during the development of the traffic guidance scheme:

- managing the impact of work vehicles and plants on the visibility of the PTCD, especially when they are located in the background
- when using PTCD at night:
 - consider the potential for driver distraction from reflective stripes on the traffic controller uniform, lights from the traffic controller wand and the indicator lights on the hand-held remote controller
 - recognise that vehicle-mounted warning devices can significantly diminish the visibility of the PTCD, especially when the vehicle is parked in the background
 - the PTCD location should be illuminated
- vehicle actuated, or fixed time operation of a portable traffic signal system should be visible to motorists at a minimum distance of 150 m
- PTCD under manual operation by a traffic controller should be visible to motorists
- located no further than 1 m from the travelled path
- mast is vertical, footing is stable, and the traffic signal is weighted down if required
- site signed to 60 km/h maximum on approach to the PTCD (as nominated in AGTTM Part 3).

2.6.3 Approved equipment for manual control of traffic

Hand-held STOP / SLOW bat

A STOP / SLOW bat measuring a minimum 1.8 m from the ground to the underside (bottom) of the STOP / SLOW bat must be used, except when a boom barrier or other traffic control devices approved by the relevant jurisdiction is used.

A STOP / SLOW bat is always to be used in conjunction with hand signals while watching approaching vehicles.

Figure 2.3: Approved STOP / SLOW bat (Aus), STOP / GO bat (NZ)

