

- the traffic controller is visible to approaching traffic (see Section 2.7.4)
- effective communication to other traffic controllers or site workers is provided (if applicable)
- the traffic controller can easily identify the last vehicle to move through before changed to STOP and is able to communicate this to other traffic controllers (if applicable)
- the traffic controller can see all PTCs in use and any traffic queues
- the station is located so that a traffic controller can commence STOP / SLOW duties in the event of a PTC system failure. In the case of only one traffic controller operating two PTCs, they should be located at the end which is on the approach to the road closure, not at the end of the road closure
- position must be subject to a risk assessment, which should consider the drivers' perspective, including the surrounding areas and possible distractions leading up to the traffic control point.
- Where line marking leading to the traffic controller is missing or hasn't been provided, additional cones or bollards may be placed at the traffic control location to further delineate the intended traffic lane. The traffic lanes on the approach to the traffic control location may also be narrowed to manage vehicles' approaching speed.

Once the traffic control station position is established, a traffic controller must ensure that:

- the Traffic Controller (symbolic) /Signals Ahead/PREPARE TO STOP/STOP HERE ON RED SIGNAL/STOP HERE WHEN DIRECTED signs and PTCs are erected correctly at the beginning of the shift
- all signs and devices are properly set up if traffic control is taken over part way through a shift
- the Traffic Controller (symbolic)/PREPARE TO STOP/STOP HERE ON RED SIGNAL/STOP HERE WHEN DIRECTED signs are removed or covered when a traffic controller is not performing traffic control duties on site
- a STOP HERE ON RED SIGNAL/STOP HERE WHEN DIRECTED sign is placed a minimum distance of 6 m from the PTC/traffic controller position (downstream), and in line with the nearest cone to the traffic controller station unless otherwise determined by a site-specific risk assessment
- where required, four cones are placed at 4 m spacing on the centreline, with the first to be 6 m from the traffic controller station, starting from the STOP HERE ON RED SIGNAL/STOP HERE WHEN DIRECTED sign position (downstream). Traffic cones are used to highlight the traffic control position, where vehicles are to stop and for traffic management purposes. A temporary hazard marker or KEEP LEFT DELINEATOR sign may be installed at the start of the row of 4 cones to direct traffic to the correct travel path if needed. The requirement for the four cones is not applicable if the traffic guidance scheme specifies otherwise following a site-specific risk assessment
- a PREPARE TO STOP sign in conjunction with the Traffic Controller (symbolic)/Signals Ahead/Boom Barrier Ahead sign is installed a minimum distance as shown in Table 2.3 from the predicted end of traffic queue (not the PTC/traffic controller position)
- there is a maximum speed limit of 60 km/h established through the worksite
- they are not partially hidden by signs and/or devices and they do not obstruct a road user's view of such signs and/or devices
- they have a clear escape path to a non-traffic (closed) section of the roadway, shoulder, footpath or median
- approaching traffic has sufficient distance to stop safely
- where possible, it is recommended traffic controllers avoid stopping large vehicles at the front of the queue and ensure vehicles have a safe braking distance
- once traffic has stopped, a traffic controller must change their position as necessary so that they are clearly visible to approaching traffic.