

Added recommended locations of the Detour marker (TM5-6A) arrow in an MMS arrangement, in response to questions regarding the placement of the detour arrow marker on MMS sign arrangements.

4.8.4 Detour marker (T5-6, TM5-6A)

Addition

When the Detour marker (TM5-6A) is used in a multi-message arrangement, the arrow panel should be located as follows:

- For an arrow pointing straight-ahead, locate the arrow closest to traffic, except where other direction related symbol panels (such as no right turn) are required in this location.
- For an arrow indicating a turn to the left or right, locate the arrow on the side of the multi-message arrangement the arrow is directing towards.

Other sizes for the truck symbolic sign exist in AS 1742.3 but not the C size MMS sign panel.

Added TM2-25-Q01C Trucks 1200x600 MMS sign panel.

4.20 Other signs and devices

4.20.1 General

Difference

Replace the Trucks (rectangle and square) row in Table 4.14:

<i>Sign</i>	<i>Sign number</i>	<i>Size, mm</i>
Trucks (Rectangle and square)	T2-25	900 x 600
	TM2-25A	600 x 600

with:

<i>Sign</i>	<i>Sign number</i>	<i>Size, mm</i>
Trucks (Rectangle and square)	T2-25	900 x 600
	TM2-25A	600 x 600
	TM2-25-Q01C	1200 x 600