

Difference

Replace the following:

Traffic control may not be required if:

- there is clear visibility past the work area and beyond it for at least 75 m, or to the end of the road if less than 75 m away and the length of the shuttle lane does not exceed 60 m
- road users have clear visibility of the work area and the opposing approach for a distance greater than 150 m and either one of the following:
 - traffic volume in both directions is 40 vph or less, and the speed is 70 km/h or less, and the length of the single lane is 60 m or less
 - the length of the single lane is 100 m or less, and GIVE WAY and ONE LANE signs are provided at one end of the shuttle lane
 - it is a residential street and the length of the shuttle is 60 m or less.

with

Active traffic control (by traffic controllers or PTCs) may not be required where:

- GIVE WAY and ONE LANE signs are provided at one end of the shuttle lane and the NO OVERTAKING OR PASSING sign is also to be erected at the start of the single lane for traffic in the opposite direction and all the following apply:
 - traffic volume in both directions is 150 vph or less
 - the traffic speed is 70 km/h or less
 - each entry to the work area is visible from the other
 - the length of the single lane or shuttle flow segment is 120 m or less, and
 - there is sight distance to opposing traffic of at least 200 m beyond the far end of the work area for traffic facing the GIVE WAY, ONE LANE assembly.