

The following must be considered when locating signs:

- Are signs appropriate for their location?
- Are signs located so that drivers' sight distance to the sign is maintained? Where they can be seen and read in adequate time by the intended road user? Sight distance for road users entering from side roads or private driveways must also be considered. The aim is to give road users sufficient warning when approaching a hazard (see Section 2.5.4)
- Are the signs placed at an appropriate height to ensure the drivers vision is maintained?
- Will signs be easily understood?
- Are repeater signs required?
- Have the risks associated with road users striking sign posts been considered?
- Do any additional measures need to be included to make the signage effective? E.g. For temporary speed limits, it is recommended that speed management treatments are included.

Sign placement should not make the sign itself, or its supports, a hazard to road workers, road users or local infrastructure (e.g. public transport). To reduce the risk of signs becoming hazards, the following treatments apply:

- Signs must be securely mounted. For road closures, consider mounting them on barricades or barriers to reduce risk of encroachment. Mounting on vehicles is also acceptable although caution and checks by an appropriately qualified person are recommended if this option is considered.
- Signs should be placed on the side of the road where work is being undertaken, though situations might arise where signs can only be put on the opposite side of the road.

Replace the dot point:

- Signs should be placed on both sides of multilane and high-volume roads to effectively communicate relevant messages to road users. For temporary speed restriction signs, refer to section 5.5.1 for requirements to install on both sides of the road. If sign duplication is not possible (e.g. vegetation, barrier, inadequate width), the designer should document an alternative to ensure all road users are able to see signs. This may involve:
 - placing signs on high temporary frames
 - duplicating signs on one side of the road