

- Signs or their supports must not obstruct visibility of other devices (e.g. signals, other signs, etc.), should not obstruct the view between different road users, or create a hazard for pedestrians or cyclists. Signs on narrow medians along the roadway might have reduced visibility. Increase the height of signs or consider using a VMS to improve visibility due to obstructions (e.g. parked cars).
- Signs must not be used where their legibility and effectiveness are compromised by contamination and/or marks and abrasions. Signs must be kept clean, especially in dusty or muddy conditions.
- Signs that conflict with the works must be removed or covered. Consider weather conditions (e.g. wind, rain) when choosing a suitable covering. It is essential that all signs at the worksite or varied travel route accurately represent the prevailing conditions at all times. Covering, altering or replacing signs may need to be approved by a RIM. Ensure that permanent signs are not damaged when doing so. Restore these signs when works are completed.
- Covering signs may be difficult due to height or size of the sign. When covering signs that are high, ensure this is done in a safe manner. All conflicting signs must be covered or removed, so it is important to identify any possible issues before implementation.
- Sign messages must not be permitted to be formed with tape, for example, Lane Status signs and mocking speed numerals in tape.
- Sign support structures must not be left in place without signs attached.

For merge tapers where the posted permanent speed limit of the road is 80 km/h or greater, the sign spacing between the lane status sign and the start of the merge taper may be increased to a distance of two sign spacings.

For merge tapers at any speed limit, where more than one lane is being closed, the sign spacing between the lane status sign and the start of the initial merge taper may be increased to a distance of two sign spacings.

A distance plate (TC2287) may be added to the lane status multi message sign to indicate the distance from the lane status sign to the start of the merge taper.

If sign duplication is not possible and the designer has chosen to repeat signs on the one side of the road, repeated signs are located a minimum of one sign spacing from the original sign.