

Entire clause now located in QGTTM to make it easier for the end user to use the document. No longer needing to go back and forth between the QGTTM and AGTTM several times.

Information which was remaining in AGTTM has been relocated to QGTTM and is highlighted blue.

See changes highlighted yellow following.

5 Past the worksite

5.3 *Separate the work area*

5.3.1 Road safety barrier system

Difference

Replace the entire Section 5.3.1 with the following:

Replace the first paragraph:

The road safety barrier system provides a physical barrier between the work area and moving traffic, designed to resist intrusion by errant vehicles and as far as practicable, redirect errant vehicles back into the travelled path. While safety barriers can be considered for all projects, this method may be inappropriate due to physical space requirements and limited edge clearances. If a road safety barrier is to be used, its design shall be based on the posted speed outside of works and not for the posted speed during works.

with the following:

The road safety barrier system provides a physical barrier between the work area and moving traffic, designed to resist intrusion by errant vehicles and, as far as practicable, redirect errant vehicles back into the travelled path. While safety barriers can be considered for all projects, this method may be inappropriate due to physical space requirements and limited edge clearances.

If a road safety barrier is to be used, its design must be based on the speed of traffic past the barrier. In most cases, this will be a semi-permanent reduced speed limit posted at the site which generally applies 24 hours a day / 7 days a week, with other further temporary reductions only applicable when required for works which are occurring. Where a general reduction in speed limit past the site has not been implemented, the permanent posted speed limit must be used as the design speed for the road safety barrier design.