

The Austroads Safety Hardware Training and Accreditation Scheme (ASHTAS) will, over time, offer courses for Safety Barrier Operative (Entry Level), Installers (Permanent and Temporary Safety Barriers), Designers (Permanent and Temporary Safety Barriers), and more. See QGTTM Part 8 Section 5.5.12 for more details.

For more ASHTAS details see the departmental web page [Austroads Safety Hardware Training and Accreditation Scheme \(ASHTAS\)](#).

Concern with the recommended maximum spacing for delineation (cones and bollards) being risk assessed so that fewer cones and bollards are required through greater spacings adopted, however safety is impacted especially for workers on foot.

Developed an approach for delineation spacing of “must” for workers on foot, but still a recommended or “should” for other uses of delineation.

See changes highlighted yellow following.

5.4 Delineate the route

Difference

Replace:

If narrower edge clearance is required, obtain approval from the relevant road infrastructure manager.

with:

If narrower edge clearances are required due to constrained geometry, the requirements of Clause 1.9 of the Queensland MUTCD Part 3 must apply.

Difference

Replace:

The spacing between delineation devices should be as detailed in Table 5.3.

with:

The maximum spacing between delineation devices should be as detailed in Table 5.3, excluding where the delineation devices are used to separate traffic from workers on foot, in which case the maximum spacing between delineation devices must be as detailed in Table 5.3.