

A guide to selecting the required temporary speed zone is provided in Table 5.5.

In subsection 'Selecting the speed limit', replace Table 5.5 with the following.

Table 5.5 – Recommended length of temporary speed zone

Temporary speed limit (km/h)	Length of zone (m)	Conditions
<40	100–200	- unusually high level of hazard for workers on foot or road users (pedestrians or cyclists) - it is impractical to separate pedestrians or cyclists from vehicular traffic in the work area
40	100 (minimum)–500 (maximum)*	- workers on foot within 1.2 m of traffic with no physical barrier - structural danger to bridges - high level of hazard for workers on foot or road users (pedestrians or cyclists)
60	150 (minimum)	- workers on foot between 1.2 m and 3 m of traffic or plant within 3 m of traffic with no physical barrier (that is, road safety barrier) - on approach to the traffic controller or PTC 60 km/h buffer zone - reduced visibility (for example, dust or smoke) - reduced standard alignment - degraded pavement surface - newly laid bituminous seal
80	500 (minimum)	- workers on foot or plant between 3 m and 6 m of traffic with no physical barrier - disturbance to alignment or pavement surface
80 (buffer)	300 (minimum)	for advance warning of a 40 km/h or 60 km/h when speed is 100 km/h or more

*Subject to a risk assessment, the maximum length for a 40 km/h temporary speed limit may be extended to 1000 m.