

- On a multi-lane road (includes divided, undivided, one-way or ramps).
- In addition to the above, any Speed Restriction sign may be duplicated (also placed on the right-hand side of the road).
- an END Speed Limit sign to terminate the temporary speed zone must be placed as per the requirements for a Speed Restriction sign above. In this case, the speed limit beyond the END Speed Limit sign will revert to the default speed limit.
- an END ROADWORK sign may be placed beyond the termination of the temporary speed zone or concurrent with a Speed Restriction sign or the END Speed Limit sign.
- If sign duplication is not practicable or possible (due to for example, vegetation, safety barrier, inadequate width), the designer must document an alternative to ensure all road users are able to see the speed limit signs (refer to Section 2.5.3 for options).

Replace the following paragraph on repeater speed limit signs:

~~Repeater signs must be used to confirm and remind users of the speed limit where the zone is long and there are locations which could seem like the temporary speed limit no longer applies (e.g. between work areas in an extended worksite), or to advise road users entering the temporary speed limit. Repeater signs must be placed on the left-hand side of the road at a maximum spacing of 500 m and on both sides on multilane roads.~~

with:

Repeater speed limit signs must be used to confirm and remind users of the speed limit where the zone is long and there are locations which could seem like the temporary speed limit no longer applies (for example, between work areas in an extended worksite), or to advise road users entering the temporary speed limit. Repeater speed limit signs may be used as required above, and must be placed on the left-hand side of the road at a maximum spacing of 500 m. On multi-lane road (including divided, undivided, one-way or ramps), repeater speed limit signs should also be placed at a maximum spacing of 500 m on the right-hand side of the roadway where practicable.