

Replace the following:

~~At the end of the temporary speed zone, the following requirements apply:~~

- ~~• A speed sign must be used to exit the temporary zone. When using this sign at the end of the roadworks, the ROAD WORK supplementary signs are not to be used in conjunction.~~
- ~~• Signs are to be placed on both sides of the carriageway where practicable.~~

with:

At the end of the temporary speed zone, the following requirements apply:

- Speed Restriction or END speed limit signs must be used to end the temporary zone.
- When using these signs at the end of the roadworks, the ROAD WORK supplementary signs must not be used in conjunction.
- Speed Restriction and END speed limit signs must be placed as per the requirements for a Speed Restriction sign above.

If it is not practicable or possible to terminate the temporary speed limit beyond the temporary speed zone by the above method

s, the END Speed Limit sign (R4-12) may be used. An example of this is where the default speed limit (typically on rural roads), road surface, alignment or other conditions will not allow the road user to travel safely at that speed. It is a legal requirement that a speed zone is terminated by:

- another regulatory speed control sign or END Speed Limit sign
- other means of traffic regulation imposed by the State.

Operational

The following apply when installing speed signs:

- Any permanent speed signs that contradict the temporary speed limit in the required zone must be covered or removed.
- Any advisory speed signs higher than the temporary speed limit in the required zone must be covered.

Replace the third dot point:

- ~~• Signs shall be placed on both sides of the roadway, where practicable to ensure road users have clear visibility of speed limit signs.~~