

with:

- Speed Restriction signs where required to be duplicated in the '**Designing the speed limit**' section should be placed on both sides of the roadway where practicable to ensure road users have clear visibility of speed limit signs.
- Temporary speed limit signs should be used together with other appropriate devices already required by other site conditions. For example, display temporary speed limit signs used for.
- worksite protection and safety in conjunction with the Workers (symbolic) sign.
- All speed limits related to road worker safety must be removed or covered when road workers, traffic controllers or plant are not on site.
- Speed limits when road workers, traffic controllers and plant are not on site should be determined with consideration of the safe passage of road users. If no hazard to road users exists, the speed limit should be returned to the permanently posted speed limit.
- Any gantries within the worksite with Variable Speed Limit or Lane Control signs must be programmed to display the temporary speed limit or turned off. Check the TMP for guidance on other large permanent signs and variable speed limit signs.
- A record of dates and times temporary speed limits are in operation must be kept, including any changes made, the name of personnel installing, changing or removing signs (see Section 2.5.3).
- Workplace safety must be considered during set-up and dismantling of signs.

Temporary speed limits should only apply while the condition that makes them necessary exists, so remove temporary speed limit signs as soon as the necessity passes. For further details on signs see Section 2.5.3.

Guidance on the use of temporary variable speed limit signs in construction and maintenance work areas on motorways is given in the [\*Guideline – Traffic Management at Works on Roads\*](#).