

3. RISK MANAGEMENT

The following details the preliminary assessment of site hazards likely to be encountered, the level of risk associated with each, and the control proposed. Note that the risk level is the level of assessed risk without the controls in place. The controls listed have been determined as being appropriate in reducing the risk to a level that is acceptable.

The hierarchy of control has been utilised to ensure that the highest practicable level of protection and safety is selected:

- Elimination
- Substitution
- Isolation
- Engineering
- Administration
- Personal Protection Equipment

In evaluating the options, a key consideration is whether the option takes traffic around, through or past the worksite.

3.1 Risk Classification Tables

Table 2: Quality Measures of Consequence or Impact

Level	Consequence	Description
1	Insignificant	• Mid-block hourly traffic flow per lane is equal to or less than the allowable lane capacity detailed in AGTTM. • No impact to the performance of the network. • Affected intersection leg operates at a Level of Service (LoS) of A or B. • No property damage.
2	Minor	• Mid-block hourly traffic flow per lane is greater than the allowable road capacity and less than 110% of the allowable road capacity as detailed in AGTTM. • Minor impact to the performance of the network. • Intersection performance operates at a Level of Service (LoS) of C. • Minor property damage.
3	Moderate	• Midblock hourly traffic flow per lane is equal to and greater than 110% and less than 135% of allowable road capacity as detailed in AGTTM. • Moderate impact to the performance of the network. • Intersection performance operates at a Level of Service (LoS) of D. • Moderate property damage.
4	Major	• Midblock hourly traffic flow per lane is equal to and greater than 135% and less than 170% of allowable road capacity as detailed in AGTTM. • Major impact to the performance of the network. • Intersection performance operates at a Level of Service (LoS) of E. • Major property damage.
5	Catastrophic	• Midblock hourly traffic flow per lane is equal to and greater than 170% of allowable road capacity as detailed in AGTTM. • Unacceptable impact to the performance of the network. • Intersection performance operates at a Level of Service (LoS) of F. • Total property damage.