

Item (Generic / Site Specific)				Risk Event	Consequence	Pre-treatment Risk			Treatment	Residual Risk		
						L	C	RR		L	C	RR
3.2.	10	2	G	Vehicle breakdown and crashes during lane restrictions causing obstruction to traffic and an increase in congestion resulting in adverse public reaction.	Adverse public reaction.	C	3	M9	Workers and Traffic Management Personnel to clear broken or damaged vehicles to assist with maintaining traffic flow through the worksite. Traffic control on-site will be equipped with mobile communications to liaise with emergency services as required. Accredited first aid personnel may be on-site to assist as necessary.	D	3	L6
3.2.	10	3	G	Temporary traffic management setups at start or end of overtaking lanes exposing overtaking vehicles to unnecessary risks resulting in serious injury or fatality.	Serious injury or fatality.	C	4	H12	Signs and devices to be installed as per the proposed Traffic Guidance Schemes, AGTTM and the MRWA Code of Practice. Length of overtaking lane may be closed to avoid exposure at start and end where safe to do so.	D	4	M8
3.2.	10	4	G	Lane closure scenarios causing right turning traffic to block through lanes at signalised and non-signalised intersections resulting in an increase of rear end collisions.	Serious injury or fatality.	C	4	H12	Dedicated right turning lanes to be maintained where possible or additional provisions provided including; turning restrictions or intersection control. Temporary speed reductions to be installed on the approach to reduce the severity of the crash should it occur. Where installed at signalised intersection and high speed midblock section, RTM approval to be sought prior to implementation.	D	4	M8
3.2	10	5	G	Tapers installed within 50m of an intersection on the un-controlled leg resulting in traffic merging within 50m of the side road/controlled leg	Damage to property	C	3	M9	An assessment is to be undertaken to determine the suitability of placing the taper within 50m of the uncontrolled leg, this should only be done when on-site constraints restrict the placement of the taper.	D	3	L6
3.2	10	6	G	Tapers installed within 50m of the controlled leg of an intersection resulting in traffic merging within 50m of the intersection	Damage to property	C	3	M9	An assessment is to be undertaken to determine the suitability of placing the taper within 50m of the controlled leg, this must only be done when absolutely necessary	D	3	L6