

Item (Generic / Site Specific)		Risk Event	Consequence	Pre-treatment Risk			Treatment	Residual Risk			
				L	C	RR		L	C	RR	
3.2.	21	2 G	Regulatory and lane status sign within mobile convoy alternated with another sign causing conflicting messages for motorists. AS 1742.3 Section 4.22.3 Message Screens (g) requires ‘When a variable message sign displaying regulatory, or lane status signs is used to substitute a static sign the message shall not be alternated with another message’.	Serious injury or fatality.	C	4	H12	Not alternating the messaging will require additional convoy vehicles or a lack in notification to road users approaching the convoy. Adequate sight distance to the vehicles VMS Board to be maintained where possible. Speed and driver compliance to be monitored by the shadow vehicle driver within the mobile convoy.	D	4	M8
3.2.	24	3 G	Speed feedback signage may have a counterproductive impact when installed as per the wording of MRWA CoP 6.16, potentially increasing the speed of motorists in areas where they would be coming to a natural stop, such as give ways, stop lines or roundabouts	Serious injury or fatality.	C	4	H12	Speed feedback signage will be omitted where its placement is not practical, such as roundabouts or giveaways/stops where traffic may exceed the expected natuaral travel speed of the road	D	4	M8
3.2	24	4 G	Speed feedback signage being used on multilane roads where more than a single lane is operational may lead to multiple vehicles passing the detectors at the same time, If one of those cars is speeding but the SFBS Detects the Non-Speeding car it may cause the other vehicle to maintain an unsafe speed through the works	Serious injury or fatality.	C	4	H12	Speed feedback signs must not be used where more than 1 lane of traffic is open past the SFBS in a single direction	D	4	M8