

- Rumble strips and/or temporary speed humps.
- Variable Message Signs (VMS) and electronic/variable speed limit signs.
- Additional Police enforcement.

Speed Feedback signage MUST be used when the following conditions are met as per the MRWA CoP Section 6.16;

- Workers on foot are not protected by a road safety barrier; and
- Works conducted at the location for a duration of 8 hours or more; and
- Traffic volume of 15,000 vpd (AADT) or more; and
- There is a temporary speed reduction of 30 km/h or more

The speed feedback display does not have to be displayed at all times e.g. the display may be turned off and the device used to gather speed data when trialling other speed control measures.

4.1.9 Excavations or Above Ground Hazards

Excavations require special consideration to ensure their structural integrity and minimise the risk of road users losing control and driving into them. The Traffic Management Assessor or Delivery Supervisor must consider the impact of longitudinal depressions and above ground road hazards adjacent to live traffic lanes during the work and where left unattended prior to the installation of any devices. Where an excavation may constitute a danger, it is required that:

- The excavation is fully covered, fenced, or backfilled when the worksite is unattended.
- The excavation is covered, fenced, or filled when work is completed.
- Only approved skid resistant plating must be used to cover an excavation.
- Fully enclose the excavation. Do not use barricades, traffic cones or plastic mesh fencing that is not supported by a solid frame.

Refer to the following table which shows the clearances between excavations, or any ground level hazard associated with the excavation, and the nearest traffic lane, relative to speed and traffic volume:

Table 16: Delineation Adjacent to Excavations – AGTMM Part 3 Table 6.1

Speed (km/h)	Traffic Volume (vpd)	Clearance to Excavation (m)	Protection Required		
			Depth of Excavation (mm)		
			50 to 250	251 to 500	>500
≤65	Any	<2.5	Option 1	Option 2	Option 3
		2.5 – 5		Option 1	Option 2
		>5			Option 1
≥70	≤1500	≤5		Option 2	Option 3
		>5		Option 1	Option 1
	>1500	≤6		Option 2	Option 3
		>6		Option 1	Option 1

**For multilane roads use volume in on direction. For two-lane, two-way roads use the sum of both directions. Any variations to the recommendation in this table need to be supported by a risk assessment.*

*** For Options 1 and 2, cones or bollards are to be placed at the top of the excavation.*

The above table is based on the following options:

- Option 1: Use traffic cones or bollards at spacing specified on the Traffic Guidance Schemes.
- Option 2: Use traffic cones or bollards spaced at 4m maximum.
- Option 3: Use a road safety barrier system as per a site-specific Traffic Management Plan.