

4.2 Road Users

4.2.1 Pedestrians

Where impacts occur to pedestrian facilities which may increase the normal use of the road facilities by people with disabilities and other vulnerable road users they must be mitigated as part of the Traffic Management advice. Traffic Management Assessor or Delivery Supervisor must detail all pedestrian treatments where significant impacts may occur. Pedestrian facilities include, but are not limited to, Bus / train stations, hospitals, clinics, surgery's, shopping centres, other retail businesses, churches, schools & universities, parks, and other recreational areas / sporting premises. Minimum path widths to be maintained as per the following table and requirements outlined in the Traffic Management Advice:

Table 17: Width Requirements for Pedestrian Paths – Austroads Guide to Road Design Part 6A

Situation	Suggested Minimum Width (m)	Additional Comments
General low volume	1.2*	- General minimum is 1.2m for most roads and streets. - Clear width required for one wheelchair. - Not adequate for commercial or shopping environments.
High pedestrian volumes	2.4	Generally at commercial and shopping areas.
For two wheelchairs to pass**	1.8	
For people with other disabilities	1.0	

**In constrained locations an absolute minimum of 1.0m should be provided. In these situations, path users should be able to detect other path users with sufficient time to respond and take appropriate actions.*

*** 1.0m absolute minimum for a single wheelchair, may be provided for short distances. 1.5m absolute minimum for one wheelchair and a pedestrian passing side by side.*

Traffic Management should be provided where these locations are adjacent to site or where a footpath or crossing has been closed due to the proposed works. This includes but is not limited to; additional Traffic Controllers on site to render assistance to vulnerable road users, footpath closures with detours via existing crossing points and additional 'Pedestrian watch your step' signage.

Consideration must be provided for the installation of temporary Traffic Management signage and devices to not adversely impact existing facilities. Sign placements must not be placed on footpaths unless enough room can be maintained to allow vulnerable road users to pass. Where this cannot be achieved, sign placement may be extended as per the tolerances listed in AGTTM or additional provisions provided on site.

Any planned works within the Perth Metropolitan area that require the closure of an existing path—designated by the Department of Transport as a Primary Route—for a period of seven (7) days or more must meet the following requirements:

- Obtain Road Planned Intervention (RPI) approval prior to implementation.
- Include a Traffic Guidance Scheme (TGS) outlining the proposed path detour and associated signage.
- Be approved by a Roadworks Traffic Manager (RTM) who has conducted a site inspection of the entire detour route.
- Undergo a compliance safety inspection of the proposed detour by an Advanced Worksite Traffic Manager (AWTM).

4.2.2 Cyclists

Where impacts occur to cyclists facilities which may increase the conflicts between cyclists and motorists they must be mitigated as part of the Traffic Management advice. Traffic Management Assessor or Delivery Supervisor must detail all cyclists treatments where significant impacts may occur.