

Cyclists facilities include, but are not limited to, on-road cyclists, principal shared paths and dedicated cyclists lanes.

Traffic Management should be provided where these facilities are adjacent or within the site. This includes but is not limited to; additional Traffic Controllers on site to render assistance to cyclists, footpath closures with detours via existing crossing points and additional 'Cyclists in Lane' signage.

Consideration must be provided for the installation of temporary Traffic Management signage and devices to not adversely impact existing facilities. Sign placements must not be placed on footpaths or dedicated cyclists lanes unless enough room can be maintained to allow cyclists to pass. Where this cannot be achieved, sign placement may be extended as per the tolerances listed in AGTTM or additional provisions provided on site.

Refer to Section 4.2.1 for closures of existing paths for more than 7 days.

4.2.3 Public Transport

The Traffic Management Assessor or Delivery Supervisor must design/specify Traffic Management to ensure no adverse impacts occur to the Public Transport Authority (PTA) network. These details will vary depending on the project, location, and time of works. Where mitigating impacts to bus/train stops or services cannot be achieved, the Delivery Supervisor must make suitable arrangements with the PTA and their service providers. Suitable notification should be provided through the Notification of Roadworks, with details of actual work dates and times.

4.2.4 Heavy and Oversized Vehicles and Loads

The Traffic Management Assessor or Delivery Supervisor must assess for impacts on the heavy and/or oversized vehicles network. These details will vary depending on the project, location, and roads. Where significant impacts occur to the network, Main Roads Heavy Vehicle Services must be notified and prior approvals may be required. Notification should be provided through the Notification of Roadworks, with details of actual work dates and times. Where detours are provided to a road within the Restricted Access Vehicle (RAV) network, the selected roads for the detour must be equivalent or higher RAV classification. Vehicle swept paths may be provided to determine whether heavy and/or oversized vehicles can pass through or around the worksite.

4.2.5 Existing Parking Facilities

The Traffic Management Assessor or Delivery Supervisor must assess for impacts to existing on-road or adjacent parking facilities within the worksite. Suitable letter drops to businesses or residents may be conducted prior to the commencement of works to provide information of any closures to parking facilities. Where possible, these facilities should be maintained, and Traffic Controllers may be provided on site to manage vehicles through the worksite. Project Delivery Supervisor to liaise with Local Government Authority on the closure of parking bays prior to the implementation of the works.

4.2.6 Access to Adjoining Properties/Business

The Traffic Management Assessor or Delivery Supervisor must assess for impacts to adjoining property and business access within the worksite. Suitable letter drops and other forms of pre-communication may be provided to warn residential and commercial premises of the potential impact of the works. Where possible, facility access should be maintained, and Traffic Controllers may be provided on site to manage