

- Scenario 1 – Activities / works within a traffic lane (open or closed)
- Scenario 2 – Activities / works within 2m of the live traffic lane on roads with a permanent speed limit of 80km/h or more.
- Scenario 3 – Implementing or removing traffic management on roads with a speed limit less than 80km/h (refer scenario 2 for speeds greater than 80km/h).

A shadow vehicle must follow approximately 40m behind the works vehicle, unless otherwise stated in the manufacturers shunt distance advice. This distance should be regularly monitored to ensure that the shadow vehicle does not drive too close to the work activity, potentially causing vehicle to shunt into work vehicles, or too far from the works activity, increasing the chance of vehicles entering in front of the shadow vehicle lowering the level of protection.

A shadow vehicle may only be omitted subject to a site-specific risk assessment, refer to the below table for shadow vehicle requirements and exceptions:

Table 19: Shadow Vehicle Scenarios – Main Roads WA Code of Practice Table 22

Scenario	Shadow Vehicle Requirements	Exceptions (Not meeting these requirements must be supported by a risk assessment as per the below)
1	Shadow vehicle must be used, the shadow vehicle must: • Be fitted with an arrow board. • Be positioned 20-40m in advance of the workers.	Risk assessment undertaken by an RTM as part of the work allocation. Mitigating factors, as a minimum, must include the use of a dedicated lookout person.
2	Shadow vehicle must be positioned 20-40m in advance of the workers. An arrow board may not be required. Crossing the road is not permitted.	Risk assessment undertaken by: • An AWTM as part of the work allocation; or • An onsite documented risk assessment undertaken by a person that holds WTM accreditation. If a risk assessment supports crossing the road a dedicated lookout person must be used.
3	Shadow vehicle may not be required, based on a risk assessment. Crossing the road to implement/remove signs or devices is not permitted.	Risk assessment undertaken by an AWTM as part of the Traffic Management Plan or an onsite documented risk assessment undertaken by a person that holds WTM accreditation. If a risk assessment supports crossing the road a dedicated lookout person must be used.