

Table 26: AGTTM Part 5 Section 4.2.2 Table 4.2: Sight Distance to the Vehicle Mounted Warning Device
(lookout person not required)

Speed (km/h)	Distance (m)
≤ 45	225
46 – 55	275
56 – 65	335
66 – 75	390
76 – 85	445
86 – 95	500
96 – 110	555
>110	A lookout person is required

The variable message sign shown on the TGS is optional only and may be used to form a secondary protection for the workers. Where the variable message sign is used it must always be within 40m of the workers.

4.8.1.3 Works on Road – Short Term Works in Traffic

This practice may be used where works are partially within a traffic lane and traffic flow in each direction can be maintained. This work should be carried out where works are on the verge and only partially within the road, maintaining minimum lane widths for each direction. Refer to AGTTM Part 5 Section 4.3 Short Term Works in Traffic and **0922-01531-STLI-004**.

This practice is best suited to the following tasks (does not include all tasks):

- Drainage pit inspections
- Minor pavement repairs
- Pavement investigation

The typical Temporary Traffic Management requirements for short term works in traffic may include a lookout person and a work vehicle fitted with a vehicle mounted warning device. This practice may only be used where all the criteria is met in the tables below. The following additional criteria outlines the use of

Table 28:

- Works are in one lane of a multi-lane road, but the remaining lane(s) are open to traffic flow.
- Where the lane width is greater than 4.5m and the work area is in the lane but is more than 1.2m from the remaining traffic flow.
- Where the works are on a road with parked vehicles adjacent to the kerb and the worker is effectively more than 1.2m from the nearest line of moving vehicles.