

Table 29: AGTTM Part 5 Section 4.3.5 Table 4.6: Sight Distance for Lookout Person

Speed (km/h)	Distance (m)
≤ 45	80
46 – 55	100
56 – 65	120
66 – 75	140
76 – 85	160
86 – 95	180
96 – 110	200
>110	220

The variable message sign shown on the TGS is optional only and may be used to form a secondary protection for the workers. Where the variable message sign is used it must be always within 40m of the workers.

4.8.1.4 Works on Road – Frequently Changing Work Area (in lane)

This practice may be used where the work area moves frequently between successive locations of a road. This work can be within the traffic lane. Refer to AGTTM Part 5 Section 4.4 Frequently Changing Work Area – In Lane and **0922-01531-STLI-005 to 008**.

This practice is best suited to the following tasks (does not include all tasks):

- Stormwater pit maintenance.
- Traffic signals and roadside sign maintenance.
- Street light maintenance.
- Pavement maintenance, testing and repairs.

Where this work practice is on high speed / volume roads within the metropolitan area, a Truck Mounted Attenuator (TMA) must be used. A TMA should be considered for all other scenarios and may be used as an option following a risk assessment. Refer to Section 4.5.1 of this document for more details. The typical Temporary Traffic Management requirements for frequently changing work area may include advanced and intermediate warning signs, a shadow vehicle, a lookout person, works vehicles and a vehicle mounted warning device.

This practice may only be used where all the criteria is met in the table below and scenario (b) may be selected when:

- Works are in one lane of a multi-lane road, but the remaining lane(s) are open to traffic flow.
- Where the lane is wide, and the work area is in the lane but is more than 1.2m from the remaining traffic flow.
- Where the works are in a low volume road and the presence of the work vehicle and workers results in traffic operating in shuttle flow.