

Table 30: AGTTM Part 5 Section 4.4.2 Table 4.7: Frequently Changing Work Area – in Lane

Criteria			Yes/No
1	The work area is (pick column that applies below):		
	(A) in traffic or within 1.2m of traffic	(B) 1.2m – 3.0m of traffic	
2	Works move frequently between successive locations		
3	The maximum work period at any one location is (pick the same column as for Criteria 1)		
	(A) 5 minutes when there are workers on foot and traffic volume is above 40vph. 20 minutes when there are no workers on foot and traffic volume is above 40vph. 1 hour at traffic volumes 40vph or less with or without workers on foot.	(B) 20 minutes when there are workers on foot and traffic volume is above 40vph. 20 minutes when there are no workers on foot and traffic volume is above 40vph. 1 hour at traffic volumes 40vph or less with or without workers on foot.	
4	A lookout person is available to warn workers on foot to vacate the roadway before the arrival of approaching traffic. If there are no workers on foot answer “Yes”.		
5	A shadow vehicle is available (Note a TMA must be provided on high speed / volume roads).		
6	A vehicle mounted warning device is displayed on both the work and shadow vehicle and the warning device is not obscured.		
7	There is a minimum sight distance from approaching road users to the shadow and the work vehicle mounted warning device of: 150m if the speed is 60km/h or less. 250m if the speed is more than 60km/h.		
8	Works do not reduce the overall width to less than the requirements for safe passage of two-way traffic flow, or one way traffic if the volume is less than 50vpd.		
9	Works do not reduce any traffic lane width adjacent to a barrier line to less than that needed to allow vehicles to proceed without crossing the line.		

Equipment or materials which are brought onto the work area should be unloaded from the non-traffic side of a stationary work vehicle, or the rear of a stationary work vehicle with a lookout person or shadow vehicle in place.

The advanced warning signs must be displayed up to 2km in advance of each work location or item of moving plant. A maximum distance of 2km between advance warning signs for opposing directions of travel must not be exceeded at any time by progressively changing their location as the work location changes. The first work area in relation to the advanced or intermediate warning signs in a succession of frequently changing work locations must be within distances specified below:

Table 31: AGTTM Part 5 Section 2.4.2 Table 2.3: Sign Spacing

Speed (km/h)	Distance (m)
≤ 55	15
56 – 65	45
> 66	Equal to the speed (km/h)

Where the works is being carried out by a large plant item and there are no workers on foot or small plant items present, the shadow vehicle must follow 40m behind the large plant item. The shadow vehicle must be in the same lane as workers that are in the road. Where the work is being carried out by workers on foot or small items of plant with, or without large plant items, the shadow vehicle must follow in the same lane as the works, 40m behind the work vehicle or workers.