

This practice may only be used where all the criteria is met in either **Table 33** or **Table 34** below:

**Table 33: AGTTM Part 5 Section 4.5.2 Table 4.9: Constantly Moving Work Area
Mobile Inspections Within a Traffic Lane**

Criteria		Yes/No
1	The inspection vehicle is either fully or partially within a traffic lane.	
2	The works area is continually moving.	
3	A vehicle mounted warning device is displayed and not obscured.	
4	The mobile road inspection is carried out providing the vehicle maintains speed: • Less than 20km/h below the speed limit or • On a road with less than 200vpd is at least 25km/h.	

**Table 34: AGTTM Part 5 Section 4.5.2 Table 4.10: Constantly Moving Work Area
Mobile Grading Works**

Criteria		Yes/No
16	The grader and other work vehicles are within the traffic lane or partially within a traffic lane.	
17	The works area is continually moving.	
18	A vehicle mounted warning device is displayed and not obscured.	
19	Traffic volumes are 3,000vpd or less for any speed environment.	
20	Works may be undertaken in bounds of up to 10km.	
21	Advanced and intermediate signage is installed on site.	

The advanced warning signs must be displayed up to 2km in advance of each work location or item of moving plant. A maximum distance of 2km between advance warning signs for opposing directions of travel must not be exceeded at any time by progressively changing their location as the work location changes. The start of the work area in relation to the advanced or intermediate warning signs in a mobile convoy must be within distances specified below:

Table 35: AGTTM Part 5 Section 2.4.2 Table 2.3: Sign Spacing

Speed (km/h)	Distance (m)
≤ 55	15
56 – 65	45
> 66	Equal to the speed (km/h)

The following should also be considered for sign placements:

- Advanced warning signs may be omitted for a section when:
 - The sight distance for the entire section exceeds 150m when the speed is 60km/h or less and a vehicle mounted warning device is displayed.
 - The sight distance for the entire section exceeds 250m when the speed is more than 60km/h and a vehicle mounted warning device is displayed.
- If the sight distance falls to less than 250m at some locations:
 - The work must be undertaken in bounds of not more than 10km in length. The sign 'ROADWORK AHEAD' and 'NEXT Xkm', where x is the length of the section but is no longer than the maximum of 10km, must be placed at each end of the section being worked on.
 - 'GRADER AHEAD' or 'ROAD PLANT AHEAD' together with 'NEXT 2km' signs must be displayed on approach to cover the sub-section with diminished sight distance. If there is difficulty turning a grader around at the end of a 2km section, the section may be extended to the next available turning point but not more than 6km in totally length. Within this extended distance, advance warning signs must be repeated at 2km intervals.

The required advanced and intermediary signs, to be erected by workers, should be done so in a manner that does not expose workers to oncoming traffic. Install signs so that the nearest edge is clear of the travelled path of vehicles and so that the signs are clearly visible to all oncoming vehicles.