

4.8.1.8 Works off Road – Frequently Changing Work Area (outside of lane)

This practice may be used where the work area moves frequently between successive locations of a road. This work must not encroach into live traffic lanes and must be restricted to shoulders, medians, verges, and footpaths. Refer to AGTTM Part 5 Section 5.3 Frequently Changing Work Area Outside of a Traffic Lane and **0922-01531-STLI-014** and **015**.

This practice is best suited to the following tasks (does not include all tasks):

- Minor cleaning of culverts, pipes, and pits.
- Tree pruning, planting, or clearing.
- Road signs or street furniture maintenance.
- Street light maintenance.
- Mowing and litter activities.
- Graffiti removal.
- Herbicide spraying.
- Road edge guidepost repairs.
- Guard rail repair and maintenance.

The preferred location of the work vehicle is adjacent to the work area with the vehicle mounted warning devices activated and parked clear of the traffic lane. The typical Temporary Traffic Management requirements for frequently changing work areas outside of traffic lanes may include advanced and intermediate warning signs, a works vehicle and a vehicle mounted warning device on the works and shadow vehicles.

This practice may be used where all the criteria is met in the tables below:

Table 43: AGTTM Part 5 Section 5.3.2 Table 5.5: Frequently Changing Work Area (Outside of Lane)

Criteria		Yes/No
1	The work area is outside of traffic lanes.	
2	Works move frequently between successive locations.	
3	The maximum work period at any one location is: • Traffic speeds 70km/h or less: ○ 20 minutes at any traffic volumes. ○ 40 minutes at traffic volumes of 150vph or less. ○ 1 hour at traffic volumes of 40vph or less. • Traffic speeds greater than 70km/h: ○ Within 1.2m of traffic. ▪ 5 minutes if there are workers on foot. ▪ 20 minutes if there are large plant items only. ○ 20 minutes if outside 1.2m of moving traffic.	
4	A vehicle mounted warning device is displayed on the work vehicle and not obscured.	
5	There is a minimum sight distance from approaching road users to the vehicle mounted warning device of: • 150m if the speed is 60km/h or less. • 250m if the speed is more than 60km/h	

The advanced warning signs must be displayed up to 2km in advance of each work location or item of moving plant. A maximum distance of 2km between advance warning signs for opposing directions of travel must not be exceeded at any time by progressively changing their location as the work location changes.