

- the vehicle mounted warning device must be operating and the hazard/arrow board used as required
- all workers must wear correct PPE
- a look out person/spotter must be used for all activities where required in accordance with AGTTM Part 5
- full co-ordination of any ITS infrastructure which may assist the Traffic Guidance Schemes removal
- the removal of the TTM signs and devices is recorded in the diary/sign register
- conduct a final drive through of the site to ensure all devices are removed and all permanent signs are reinstated or uncovered.

If it is considered too dangerous due to speed or volume, then consideration needs to be given to adopting a mobile convoy (refer to AGTTM Part 4) or other controls e.g. traffic control to hold traffic during removal under its own Traffic Guidance Schemes. A different sequence may need to be adopted to address any site-specific circumstances and can be approved by Traffic Management Designer.

7.2.7 Removal Process

The general procedure for removing a site is the:

1. work area (devices in reverse order)
2. affected side of roadway (signage in direction of travel)
3. non-affected side of roadway (signage and devices in direction of travel)
4. side roads (closure devices then signage in direction of travel)
5. detours (in direction of travel).

7.2.8 Removal Order for Signs and Devices

The scenarios described in this Section are designed to encourage workers to review the safest process for removal of a Traffic Guidance Schemes. Many factors can influence the sequence of removal including but not limited to road geometry, hills, crests, curves, surface condition, lane widths, shoulder width, VPD, peak traffic flows, road user travel speed, road user make up (e.g. % of heavy vehicles or cyclists), lighting & time of day and weather.

AGTTM Part 6, Section 6.4 gives several scenarios for the typical removal with diagrams and steps to facilitate safe removal. These diagrams can be referred to when Traffic Management Implementer's are preparing for removal. The scenarios include:

- Two-way road - lane closure
- Two-way road (lateral shift)
- Two-way road - lane closure with side road intersections
- Multi-lane un-divided road - lane closure
- Multi-lane divided road - left or right lane closure

7.3 Traffic Control Devices

7.3.1 Requirements for Signs

All signs used shall conform to the designs and dimensions as shown in Australian Standard AS 1742.3, AGTTM and the CoP.

Prior to installation, all signs and devices shall be checked by the Site Supervisor or a suitably qualified person to ensure that they are in good condition and meet the following requirements:

- Mechanical condition - It is required for items that are bent, broken or have surface damage not be of use.
- Cleanliness - Items should be free from accumulated dirt, road grime or other contamination.