

- Colour of fluorescent signs - fluorescent signs whose colour has faded to a point where they have lost their daylight impact shall be replaced.
- Retro reflectivity. - Signs for night-time use whose retro reflectivity have degraded either from long use or from surface damage and does not meet the requirements of AS1906 need replacement.
- Battery operated devices - shall be checked for lamp operation and battery condition.

Where signs either do not conform to the requirements of AS 1742.3, AGTMM or MRWA CoP or would fail to pass any of the above checks, need replacement on notice.

Signs and devices shall be positioned and erected in accordance with the locations and spacing as shown on the drawings. Erection and positioning of all signs are to be such that:

- They are properly displayed and securely mounted;
- They are within the driver's line of sight;
- They cannot be obscured from view;
- They do not obscure other devices from the driver's line of sight;
- They do not become a possible hazard to workers or vehicles; and
- They do not deflect traffic into an undesirable path.

A suitable opaque material shall cover signs and devices erected before they are required. Immediately prior to the commencement of work, the cover may be detached. Where there is a potential for conflict of information between existing signage and temporary signage erected for the purpose of traffic control, it is required the existing signs be covered. It is required that the sign not be seen once the material covering is placed on the sign, under all conditions i.e. day, night and wet weather. As to not cause damage, ensure care to the existing signs when being covered by material or by adhesive tape.

7.3.1.1 Securing Signs and Devices

All signs and devices must be positioned and erected so that they are properly displayed and securely mounted. The mountings should be stable in windy conditions and from the effects of high-speed moving traffic. Signs must have additional support and be located with adequate lateral clearance from the travelled way. The following scenarios are more likely to encounter fallen signs but are not limited to:

- Where windy conditions are expected.
- The road is used by road trains.
- The permanent speed is 80km/h or greater.

The following options should be considered, using a risk management approach, to mitigate the risk of signs falling over and/or not being properly displayed:

- Sandbags (or similar) weighing 10-15kg on all legs.
- Regular monitoring and maintenance in place to rectify fallen signs.
- Use of Variable Message Signs in advance of the work site.

There may be a need to use a combination of the above methods on any particular site and some form of monitoring the signs will always be required.

When using cones or bollards at high-risk locations and it is expected they will blow over due to windy conditions, heavy vehicles or traffic speed the following must be considered to ensure additional stability:

- Bollards to have a base of 12kg (or two 6kg bases can be used)
- Cones to have a minimum of 6kg (or two 3kg cones stacked on top of each other).

Examples of high risk locations include but are not limited to lateral shifts on high speed roads, devices separating the work area and devices delineation excavations.