

7.3.2 Tolerances on Positioning of Signs and Devices

Where a specific distance for the longitudinal positioning of signs or devices with respect to other items or features is stated, for the spacing of delineating devices or for the length of tapers or markings, the following tolerances may be applied: -

1. Positioning of signs, length of tapers or markings:
 - (i). Minimum, 10% less than the distances or lengths given.
 - (ii). Maximum, 25% more than the distances or lengths given.
2. Spacing of delineating devices:
 - (i). Maximum, 10% more than the spacing shown.
 - (ii). No minimum.

These tolerances shall not apply where a maximum, minimum or a range is already stated for a distance, length or spacing.

7.3.3 Flashing Arrow Signs

Flashing arrow signs will comprise of a matrix of lamps in the form of an arrow that is flashed in a cyclic manner to provide advance warning of a temporary diversion. It includes a backing board for the lamps together with ancillary equipment necessary for mounting and operating the sign, and reducing its light output (dimming) for night-time use. Flashing yellow signs shall be in accordance with AS/NZS 4192. Illuminated flashing arrow signs may also be constructed of variable message LED type signs to provide the same or a similar diversion arrow effect. The following three size designations must be used:

Table 49: Illuminated Flashing Arrow Sign Size – Main Roads Code of Practice Section 6.10 Table 16

Circumstance	Size
Lane closures or mobile works on roads with a permanent speed of 60km/h or less.	Size A 1260 x 650 mm
Lane closures or mobile works on roads with a permanent speed of 70km/h or more.	Size B 1500 x 770 mm
Lane closures or mobile works on: • Any Freeway; or • Multilane roads with a speed of 90km/h or more and 15,000vpd or more; or • Where a high level of long distance advance warning is desirable for safety.	Size C 2400 x 1200 mm

High intensity flashing lamps may be used in conjunction with this sign provided that the lamps are either appropriately shielded or laterally or vertically displaced from the edge of the sign to avoid visually corrupting the arrow shape or its directional effect.

Requirements for the flashing of different patterns of the lights are as follows:

- When traffic is expected to pass the sign on a particular side and can do so in safety, i.e. it is not required to seek a gap in oncoming traffic, the bar of the arrow and the barb directing traffic to that side shall be flashed.
- When the sign is used to give a general warning of works activity ahead including mobile works, but either the sign is located clear of the traffic path or the display of an arrow would not be appropriate for some other reason, either the bar of the arrow only or the four corner lights at the extremities of the barbs shall be flashed. In the latter case diagonal pairs should be flashed alternately.