

**Table 51: 'Past' spacing of traffic cones, bollards and post-mounted delineators – AGTTM Part 3 Table 5.3**

| Purpose and usage                                        | Speed (km/h)* | Recommended maximum spacing (m) |
|----------------------------------------------------------|---------------|---------------------------------|
| <b>For traffic cones and bollards**</b>                  |               |                                 |
| All purposes                                             | <55           | 4                               |
|                                                          | 56 - 75       | 12                              |
|                                                          | >76           | 18                              |
| Protecting freshly painted lines                         | 56 – 75       | 24                              |
|                                                          | >76           | 60                              |
| Centreline on approach to a traffic controller position. | All speeds    | 4                               |
| Crossover for contraflow                                 | All speeds    | 2                               |
| Taper at traffic control station                         | All speeds    | 4                               |
| <b>For post-mounted delineators</b>                      |               |                                 |
| All purposes                                             | <75           | 24                              |
|                                                          | >76           | 60                              |

\*Use the speed limit where the cones and bollards are installed.

\*\*Consider whether cyclists are using the road shoulder or bike lane and whether an appropriate alternative facility be provided before installing traffic cones or bollards in the area. Where possible, place bollards to maintain a safe cycling facility.

### 7.3.5 Variable Message Signs

Variable Message Signs usage must be in accordance with section 3.16.6 in AS1742.3 and the displays shall conform to the following:

**Table 52: Display Dimensional Requirements – AS 4852.2 Table 5.1**

| Size range (type) | Height to-width ratio | 85 <sup>th</sup> percentile approach speed (km/h) | Min. legibility distance (m) | Min. equivalent character height (mm) | No. of lines | Characters per line | Min. luminous intensity half-angle (degrees) | Min. character spacing (pixels) | Min. line spacing (pixels) |
|-------------------|-----------------------|---------------------------------------------------|------------------------------|---------------------------------------|--------------|---------------------|----------------------------------------------|---------------------------------|----------------------------|
| A                 | 7:5                   | ≥50 and ≤60                                       | 100                          | 200                                   | 3            | 8                   | 15                                           | 1                               | 2                          |
| B                 | 7:5                   | >60 and ≤90                                       | 200                          | 320                                   | 3            | 8                   | 6                                            | 1                               | 2                          |
| C                 | 7:5 or 8:5            | >90                                               | 300                          | 400                                   | 3            | 8                   | 6                                            | 1                               | 2                          |

**NOTE:** Each sign should have less than 25 x 47 pixels for its message display.

Variable message signs are usable at or near a work site to carry warning or other messages relating to the works. Variable message signs displaying unrelated messages at a work site are to be turned off.

| <b>Mandatory requirements of VMS</b> |                                                                                                                                                    |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| 1                                    | VMS used must be Type C sized and solar powered when trailer mounted                                                                               |
| 2                                    | Message no more than 4 words or numbers on any one screen. Message line must be centred to the screen.                                             |
| 3                                    | Message no more than 2 screens of display per VMS.                                                                                                 |
| 4                                    | Refer to table 5.1 above, for letter size. Lettering to be easily read by road users at the prevailing speed of traffic.                           |
| 5                                    | Messages shall be as per the Traffic Guidance Schemes or as approved by the Road Infrastructure Manager                                            |
| 6                                    | Messages shall be yellow text on black background.                                                                                                 |
| 7                                    | Variable speed limit signs, where used shall be in accordance with AS 1742.4 and shall reinforce an established speed limit existing or temporary. |
| 8                                    | Regulatory Control, any regulatory or lane status signs must not be alternated with another message.                                               |