

A variation to the standards has been attached to this TMP for point 8, during mobile work operations due to limited number of VMB signs in a convoy to display all the required messages.

7.4 Site Access for Works Vehicles

When determining methods of entry and exit to the worksite, the following shall be considered:

- approach routes
- where possible avoid placing access points on curves
- visibility at the access point (e.g. where fences or signs obstruct sight distance) shall ensure that traffic entering or leaving the worksite can see and be seen by other road users, and that vulnerable road users such as children, are visible to traffic entering or leaving the site
- sight distance to access points in or out of the worksite to pedestrian or cyclist paths to prevent conflict
- a clearly determined site entrance for all approaching vehicles that is clearly communicated and delineated.
- radio communication between traffic management crew and worksite traffic
- the differing speeds of work vehicles and general traffic
- deceleration and acceleration zones either side of an access point for work vehicles entering and exiting the worksite
- the need for general traffic to be stopped for work vehicles entering and exiting
- additional acceleration lane for vehicles exiting the worksite
- the need for multiple access points for entry and exit
- additional special access points for heavy or over-dimensional vehicles (e.g. construction, work vehicles) that have difficulty entering and leaving a normal access point
- the assistance of traffic control (e.g. traffic controller or portable device) at entry and exit points.

Access points should be located a minimum distance equal to the speed limit measured from the access point to any intersection, on or off-ramp, taper or other obstruction that restricts visibility to the access point. For example, a speed limit of 70 km/h requires the access point to be located a minimum distance of 70 m from the large tree obstructing the visibility of approaching vehicles, to the access point. This guidance is for access points only and not to be used for sight distance to a sign.

Entry and exit of vehicles through an access point should occur in the direction of general traffic flow with their vehicle mounted flashing lamps switched on to warn road users. Vehicles may reverse into a closure where risks are managed, traffic volumes are low enough and there is traffic control in place to ensure the vehicle itself is not a hazard and safety is provided for road workers and road users.

Vehicles leaving a site at a signal-controlled intersection, through a red signal, shall be deemed to be entering the public road illegally. As such, an alternative exit point shall be located away from the signal-controlled intersection at a minimum distance equal to the speed.

At all times, work vehicles are to comply with the road traffic code when conducting themselves to and from worksites an example is as follows:

- Access points shall be notified to work personnel and suppliers and vehicles shall:
 - Decelerate slowly and signal their intention by indicator to leave the traffic stream;
 - Activate the vehicle's rotating yellow lamp, once a speed of 20 km/h. has been reached and at least 50m prior to the exit location.
 - Switch on the vehicle hazard lights once the vehicle is stationary.
 - Where risks associated with unassisted exit or entry to or from the traffic stream are high, Traffic Controllers are to assist entry and exit movements.
- Vehicles fitted with rotating amber lamps shall have the vehicle's rotating lamp activated prior to entering the traffic stream and shall undertake the following:
 - Switch off the vehicle hazard lights;