

Speed feedback Signage not installed on approach to Give way, stop line and roundabouts where the works is after these points	MRWA CoP Section 6.16 Speed feedback signs must be used at static worksites on Main Roads' roads when all the following apply: • Workers on foot are not protected by a road safety barrier; and • Works conducted at the location for a duration of 8 hours or more; and • Traffic volume of 15,000 vpd (AADT) or more; and • There is a temporary speed reduction of 30 km/h or more Page 70	Traffic may unintentionally increase speed to match the Temporary speed limit in areas where traffic coming to a natural give way or stop	Spotters are to be used within the work area to provided early warning to workers to potentially errant vehicles	D	4	M8
Speed feedback Signage not installed where there are more than one lane open past the speed feedback sign	MRWA CoP Section 6.16 Speed feedback signs must be used at static worksites on Main Roads' roads when all the following apply: • Workers on foot are not protected by a road safety barrier; and • Works conducted at the location for a duration of 8 hours or more; and • Traffic volume of 15,000 vpd (AADT) or more; and • There is a temporary speed reduction of 30 km/h or more Page 70	Where multiple lanes are open past the SFBS there is the possibility that speeding vehicles may pass the SFBS at the same time as the Non-Speeding vehicles, resulting in incorrect speeds for that vehicle being displayed That vehicle may then go on to continue at the incorrect speed through the works	Speed feedback signs must not be used where more than 1 lane of traffic is open past the SFBS in a single direction	D	4	M8