

A		B		C		D		E		F		G		H		NOTES	
SCENARIO 3A:												IMPLEMENTATION PROCEDURES				DOCUMENTATION ON-SITE VARIATIONS MUST BE APPROVED BY THE TRAFFIC MANAGEMENT SUPERVISOR, THAN AN ON-SITE VARIATION MADE AND CHANGES RECORDED IN THE DAILY DAIRY. FOR MORE INFORMATION REFER TO SECTION 9.3 OF THE TMP. 1. TM VEHICLE SHALL BE ANY OF THE FOLLOWING: 1.1. TRAFFIC MANAGEMENT UTE 1.2. UTE WITH ARROW BOARD 1.3. CONE TRUCK 1.4. MR TRUCK 1.5. HR TRUCK 1.6. TRUCK MOUNTED ATTENUATOR 2. THIS DRAWING IS FOR IMPLEMENTATION ONLY AND MUST BE USED IN CONJUNCTION WITH AN APPROVED TRAFFIC MANAGEMENT LAYOUT TGS. 3. THIS DRAWING IS TO BE USED AS A GUIDELINE FOR THE TYPICAL SIGNAGE INSTALLATION AND MAY CHANGE DEPENDING SITE REQUIREMENTS. 4. THIS SCENARIO IS TO BE USED WHERE THE TM VEHICLE MUST PARK IN THE LANE DUE TO A ROAD SIDE HAZARD OR SHALLOW VERGE. 5. TC AND TM VEHICLE TO MAINTAIN 20-40M FROM SHADOW VEHICLE AT ALL TIMES. 6. DRIVER OF SHADOW VEHICLE MUST ACT AS SPOTTER TO WARN OF ERRANT VEHICLES. 7. SHADOW VEHICLE MUST BE REPLACED WITH A TMA ON HIGH SPEED/VOLUME ROADS AND FREEWAYS. REFER TO THE TMP OR MAIN ROADS REQUIREMENTS FOR THE USE OF TRUCK MOUNTED ATTENUATOR POLICY FOR MORE INFORMATION.	
DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES												SCENARIO 3A: - EACH SIGN IS TO BE INSTALLED AS PER TGS-IW-002 SCENARIO 3. - THIS SCENARIO IS TO BE USED ON DUAL CARRIAGEWAYS WITH A POSTED SPEED 80km/h OR GREATER AND WHERE THERE IS NOT ENOUGH ROOM TO SAFELY PARK IN VERGE/MEDIAN. - TC AND TM VEHICLE TO REMAIN 20-40M FROM SHADOW VEHICLES AT ALL TIMES, WHERE CONGESTION OCCURS CONVOY TO MOVE OFF ROAD AT SAFE LOCATION AND LET VEHICLES PASS. - SHADOW VEHICLE MUST BE REPLACED WITH A TMA ON HIGH SPEED/VOLUME ROADS AND FREEWAYS. REFER TO THE TMP OR MAIN ROADS REQUIREMENTS FOR THE USE OF TRUCK MOUNTED ATTENUATOR POLICY FOR MORE INFORMATION. - VEHICLE TO RESET AT START OF SIGNAGE INSTALLATION FOR SIGNAGE ON THE OTHER SIDE OF THE ROAD.					
SCENARIO 3A:																	
DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES																	
SCENARIO 3B:												SCENARIO 3B:				FOR IMPLEMENTATION ONLY	
DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES												- EACH SIGN IS TO BE INSTALLED AS PER TGS-IW-002 SCENARIO 3. - THIS SCENARIO IS TO BE USED ON TWO WAY ROADS WITH A POSTED SPEED 80km/h OR GREATER AND WHERE THERE IS NOT ENOUGH ROOM TO SAFELY PARK IN VERGE/MEDIAN. - TC AND TM VEHICLE TO REMAIN 20-40M FROM SHADOW VEHICLES AT ALL TIMES, WHERE CONGESTION OCCURS CONVOY TO MOVE OFF ROAD AT SAFE LOCATION AND LET VEHICLES PASS. - SHADOW VEHICLE MUST BE REPLACED WITH A TMA ON HIGH SPEED/VOLUME ROADS AND FREEWAYS. REFER TO THE TMP OR MAIN ROADS REQUIREMENTS FOR THE USE OF TRUCK MOUNTED ATTENUATOR POLICY FOR MORE INFORMATION. - VEHICLE TO FIND A SUITABLE PLACE TO LEGALLY TURN AROUND TO INSTALL SIGNS IN THE OPPOSING DIRECTION.					
SCENARIO 3B:																LEGEND EXISTING ROAD TC MOVEMENTS TM VEHICLE MOVEMENTS	
DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES																	
SCENARIO 3B:																METROPOLITAN REGIONS TRAFFIC MANAGEMENT BRANCH WATERLOO CRESCENT TELEPHONE (08) 138 138 EAST PERTH 6004	
DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES																	
A		B		C		D		E		F		G		H		DATE OF DRAWING 2025 JULY LOCAL GOVERNMENT AUTHORITY - ROAD AUTHORITY MAIN ROADS WA CHECKED BY TYLER HARTLEY ACCREDITATION RTM-0066 DESIGNED BY MICHAEL REED ACCREDITATION AWTM-23-II536-02 GENERIC TRAFFIC GUIDANCE SCHEME IMPLEMENTATION WORK SETUPS CONTINUOUS SIGNAGE IMPLEMENTATION TGS-IW-002 SCENARIO 3 DRAWING NO 0922-01531-IW-008C REVISION 6	